DESIGN WITHIN REACH



ThinAir® ADA-COMPLIANT HAND DRYER

The ThinAir® Hand Dryer is a high-efficiency model that is surface-mounted and ADA-compliant. ThinAir dries hands in 15 seconds*, uses 960 watts or less and has a slimmer profile to meet ADA compliance standards. The ThinAir Hand Dryer features adjustable speed and sound control, optional on/off heat and a washable pre-filter.

ThinAir® HAND DRYER

MODELS: TA - ABS -VOLTAGE (See Chart)





TA-ABSWhite Polymer (ABS) With SanaFor™ Antimicrobial Additive



FEATURES & BENEFITS

✓ 15 Second Dry Time*

Less than 960 Watts; as low as 333 Watts with heat turned off

Meets 4" ADA protrusion guidelines to accommodate the visually impaired ✓ Adjustable Speed and Sound Controller

On/Off Heat

✓ Washable Pre-Filter

5-Year Limited Warranty

OPTIONAL ACCESSORIES

MICROBAN® Antimicrobial Wall Guards: 89W (White), 89B (Black) Stainless Steel: 89S (Brushed)

ADA COMPLIANCE

ADA guidelines state that fixtures mounted above 27" must not protrude more than 4" from the wall.



37^a

Maximum: 48" Recommended: 37"

OVERALL DIMENSIONS

Width: 9 5/32" (233 mm) **Height:** 13 15/16" (354 mm) **Depth:** 4" (102 mm)

ACTIVATION

Automatic Sensor Activated

MOUNTING

Surface-Mounted

WEIGHT

TA-ABS: 8 lbs. (3.6 kgs.)

ELECTRICAL

Units are Single Phase; 960 Watts or as low as 333 Watts (without heat) and available as specified in:

110-120V	8A	60 Hz	c (UL) us
208-240V	4A	50/60 Hz	c (UL) us
230V	3.9A	50 Hz	C€

SUGGESTED MOUNTING HEIGHTS

from floor to bottom of dryer:

-		
Men	45"	(114 cm)
Women	43"	(109 cm)
Teenagers	41"	(104 cm)
Small Children	35"	(89 cm)
Handicapped	37"	(94 cm)





RoHS





^{*} Dry time based on third party testing performed by SGS International on standard Thin Air hand dryer to 0.2g or less of residual moisture.

